



2016-II GLASS

Elastic wheels

For removing of metal coating from glass with portable grinders, vertical stationary machines , cutting tables (bridge machines)

Machine	Diam	Thickness	Bore	Spec		Color code	Max speed	Sysnr
		(T)						
Portable grinder	125	10	25,4	A80-BE1555/32	standard	brown	32 m/s	197789
Portable grinder	125	10	76,2	A1507-BE15TF	standard	brown	20 m/s	814865
Portable grinder	150	10	25,4	A80-BE1555/32	standard	brown	32 m/s	790107
Portable /Stationary	180	10	76,2	A1507-BE15TF	standard	brown	20 m/s	328501
Stationary	200	10	76,2	A80-BE1556	standard	blue	20 m/s	875523
Bridge machine	200	20	76,2	A80-BE1556	standard	blue	20 m/s	892294
Bridge machine	200	25	76,2	A80-BE1556	standard	blue	20 m/s	72799
Stationary	200	10	76,2	A1507-BE15TF	long life	brown	20 m/s	312972
Bridge machine	200	20	76,2	A1507-BE15TF	long life	brown	20 m/s	834024
Bridge machine	200	25	76,2	A1507-BE15TF	long life	brown	20 m/s	782837
Bridge machine	200	20	76,2	89A807-BE14TF	low rpm speed	yellow	16 m/s	621089

Minimum order quantity	15 pieces	Ø 125 - 150
	10 pieces	Ø 180 - 200

For bore 76 availability on demand, with the same price as bore 76,2
 Delivery time : 8 working weeks

Codes for different thickness will be processed on demand

Price	for thickness 10-14	same as T10
	for thickness 15-20	same as T20
	for thickness 21-27	same as T25

Application recommendations

For stationary/bridge machines:

Start with BLUE type (BE1556) and move to BROWN (BE15TF) for higher lifetime -verifying if cutting capacity is still suitable

Working parameters:

Pressure applied can change from 0,5 to 3,0 bars

Linear speed is based on coating and wheel type

The suitability of the wheel with the rpm of the machine is a parameter always to be checked