

CORE DRILLING SYSTEM **DRS 162★★**

Core drilling up to Ø 162 mm



Powerful 2,5 kW Motor



One speed for drilling diameters up to 162 mm.



Space-saving attachment facility via dowel foot.

The DRS162** drill system is the ideal core drill entry model. The drill motor and drill rig complement each other perfectly and form a single unit. The preset speed and compact, light-weight construction guarantee easy

handling and user-friendliness. An integrated PRCD safety switch ensures maximum safety. Optional vacuum plate offers more flexibility in fixing the system.

System & Accessories

Technical data

Drill rig (integrated)

Bore hole diameter	40–162 mm
Max. drill bit length	556 mm

Drill rig (integrated)

Drill diameter range in concrete ca.	40 – 162 mm
Nominal power	2,5 kW
Nominal current	11,5 A
Nom. voltage/frequency standard	230V / 50Hz
Load speed	450 rpm
Cooling	Air cooling
Tool attachment external thread	1 ¼ "
Tool attachment internal thread	½ "
Operation	Drill rig operation
Application	Wet
Electronic overload cut-out	
Mechanical overload cut-out	
PRCD protection switch	

Design

Aluminium dowel foot
Feed using hand crank
Adjustable feet (M12)
1 handle
Motor fixed integrated

Dimensions & Weight

Length	365 mm
Width	185 mm
Height	855 mm
Weight (drilling system)	15,5 kg

System & Accessories

Core drilling system DRS162**

10990700	Core drilling system DRS162** / 230V (dowel feet)
----------	---

Accessories

974270	Extraction device for core bits
977353	Extraction device for cores
10991465	Water tank 10 l
10993961	Vacuum plate complete
984035	Vacuum pump
975372	Vacuum pump CV 45 l/min, 0,8 bar CH
975381	Vacuum hose complete 3 m